


Codan 2657 Gas Hose



Codan 2657 - EN ISO 3821:2019 / EN 16436-1:2014+A3:2020 Class 3

Flexible, smooth, black hose for liquefied petroleum gas (LPG), propane/butane, to EN ISO 3821:2019 and EN 16436. The hose is primarily for use of assemblies of LPG applications.
Important: The European Committee For Standardization has introduced new standards for LPG hoses: EN16436-1:2014+A3:2020. Click [here](#) [3] to read about the new regulations.

Type nr. 2657
Application: Gas Hose
Standard Length: 50 metres
Working Temperature: -30°C to 90°C
Inside: NBR
Colour: Black
Reinforcement: Polyester
Outside: CR
Colour: Black
Standards: EN ISO 3821:2019 / EN 16436-1:2014+A3:2020 Class 3
Std. branding: -

| Inside dia. (mm) | Outside dia. (mm) | Working Pressure BAR | Burst Pressure BAR | Bend Radius (mm) | Weight (g/m) | Product code |
|---------------------|----------------------|-------------------------|-----------------------|---------------------|-----------------|-----------------|
| 4,0 | 12,0 | 30 | 90 | 35 | 120 | 2657004 |
| 6,3 | 16,3 | 30 | 90 | 45 | 185 | 2657006 |

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.



Codan Rubber A/S Værkstedsvvej 45-49, DK-4600 Køge, Denmark Tel. +45 56 64 64 64 Mail: info@codan.com
www.codan.com

03/10/2024